

### ProSecure<sup>®</sup> Unified Threat Management Appliance **UTM Series**




### Unified Gateway Security for Growing Businesses – Without Compromise

The ProSecure UTM series of all-in-one gateway security appliances combine best-of-breed enterprise-strength security technologies from Commtouch<sup>®</sup>, Mailshell<sup>™</sup>, and Sophos<sup>™</sup> with patent-pending Stream Scanning Technology to protect businesses against today's Web, email, and network threats. Malware hosted on Web pages, phishing attacks, spam, virus infected emails, hackers, denial-of-service attacks, and other threats are now all part of a regular repertoire of sophisticated blended attacks that bypass traditional firewalls with ease. Because comprehensive network security solutions require an abundance of processing power to examine network traffic in real time, existing all-in-one security solutions often use rudimentary security technologies that trade comprehensiveness for speed. True security must satisfy the requirements in both speed and coverage.


### All-in-one Network Security - Redefined

ProSecure Unified Threat Management (UTM) Appliances combine performance with comprehensive security coverage. Patent-pending Stream Scanning Technology enables the ProSecure UTM to utilize virus and malware threat databases from ProSecure and Sophos<sup>™</sup> that are over one million signatures in size - up to 400x more comprehensive than legacy all-in-one platforms at a speed that is up to 5x faster than conventional methods. This architecture, combined with best-of-breed hybrid in-the-cloud Web filter and anti-spam technologies along with proven firewall, IPS, and VPN functionality, form the ideal growing business gateway security solution.



### **Revolutionary Stream Scanning Platform**

Given the high performance requirements of scanning latency sensitive Web traffic, incorporating enterprise-grade security software technologies onto traditional all-in-one platforms has been a very difficult task. Traditional batch-based scanning methods introduce large amounts of latency into network traffic and can slow Web browsing to a crawl. All-in-one solutions in the past have tried to overcome this by minimizing the malware signature set, scanning only a select few file types, or by avoiding Web scanning altogether. This exposes an entire vector of the network to malware-based attacks. The ProSecure UTM features patent-pending Stream Scanning Technology which analyses data streams as they enter the network. This significantly reduces latency and allows the use of an extensive malware signature library for scanning – thus offering an unprecedented combination of speed and coverage in an all-in-one solution.



mailshell<sup>™</sup> SOPHOS

# ProSecure UTM Features and Highlights

### Best-of-breed Anti-malware Engine

- Enterprise-class malware scan engineUp to 400 times the coverage of
- Op 10 400 lines the coverage of legacy all-in-one solutions
   - Over 1 million malware signatures
- Over I million malware signatures
- Hourly automatic signature updatesZero hour heuristic based threat
- protection
- ProSecure Patent Pending
  Stream Scanning Technology
- Data streams are processed as they enter the network
- Low latency Web traffic scanning
- Distributed Spam Analysis Anti-spam Technology
- Hybrid in-the-cloud architecture
  Gathers threat data from over 50 million global sources
- New spam is classified and detected within minutes
- No learning period, works right out of the box
- Minimal false positives
- Distributed Web Analysis URL Filtering
- Hybrid in-the-cloud architectureHundreds of millions of
- categorized URLs – Real-time classification into
- 64 categories

## IM and P2P Application Control

- Blocks access to public IM clients
- Blocks peer-to-peer (P2P) clients
- Preserve productivity and save bandwidth



labs



#### SSL & IPsec VPN Remote Access

- SSL VPN clientless remote access, anywhere, anytime
- IPsec VPN secure site-to-site tunnels and client-based remote access
   No additional licenses to purchase
- Built-in SPI Firewall
- Dual WAN Gigabit Firewall\* provides load balancing and failover
- Four Gigabit LAN ports, one configurable hardware DMZ port
- Stateful packet inspection (SPI)
- Denial-of-service (DoS) protection
- IPS prevents hackers from penetrating the network perimeter

#### Simple Setup, Ease of Management

The ProSecure UTM will easily replace any existing firewall or router. A simple 10-step setup wizard guides you through installation and the UTM will be up and running in minutes. Administration is performed through an intuitive Web-based interface. Set granular policies and alerts, check summary statistics and graphical reports, drill down to IP address-level data, and integrate log data with standard network management tools using SNMP. Malware and IPS signature, software, and firmware updates are all handled by the UTM - online and automatically.

For many administrators and IT personnel one of their biggest nightmares is the management of individual licenses or "seats." Buying additional licenses when computers and personnel are added to the network is time-consuming and costly. The ProSecure UTM offers Web and email protection subscriptions with no "per-user" licensing.

#### **UTM SERIES COMPARISON**

MODEL	UTM5	UTM10	UTM25	UTM50	
SIZING GUIDELINES					
Average Anti-virus Throughput <sup>1</sup>	15 Mbps	20 Mbps	25 Mbps	45 Mbps	
Stateful Packet Inspection Firewall Throughput <sup>1</sup>	90 Mbps	90 Mbps	127 Mbps	950 Mbps	
Maximum VPN Throughput <sup>1</sup>	40 Mbps	50 Mbps	70 Mbps	200 Mbps	
Maximum Concurrent Connections <sup>1</sup>	8,000	12,000	27,000	40,000	
VLANs	255	255	255	255	
CONTENT SECURITY					
Web and Email Scanned Protocols	HTTP, HTTPS, FTP, SMTP, IMAP, POP3				
Stream Scanning	٠	•	•	•	
Inbound and Outbound Inspection	•	•	•	٠	
Signature-Less Zero Hour Protection	•	•	•	٠	
Malware Signatures	1.2 Million	1.2 Million	1.2 Million	1.2 Million	
Automatic Signature Updates	Hourly	Hourly	Hourly	Hourly	
Web Content Filters	Filter By: HTML Body Keywords, File Extension				
Web Object Filters	ActiveX, Java™, Flash, JavaScript™, Proxy, Cookies				
Email Content Filters	Filter By: Subject Keywords, Password-protected Attachments, File Extension, File Name				
Distributed Spam Analysis	•	•	•	•	
Distributed Spam Analysis Supported Protocols	SMTP, POP3				
Anti-spam Real-time Blacklist (RBL)	•	•	•	٠	
User-defined Spam Allowed/Block Lists	Filter By: Sender Email Address, Domain, IP Address, Recipient Email Address, Doma			Address, Domain	
Distributed Web Analysis w/ 64 categories	٠	•	•	٠	
Instant Messaging (IM) Control	MSN <sup>®</sup> Messenger, Yahoo! <sup>®</sup> Messenger, mIRC, Google Talk				
Peer to Peer (P2P) Control	BitTorrent™, eDonkey, Gnutella				
Maximum Number of Users	Unlimited				
FIREWALL FEATURES					
Stateful Packet Inspection (SPI)	Port/Service Blocking, Denial-of-service (DoS) Prevention, Stealth Mode, Block TCP Flood, Block UDP Flood, WAN/LAN Ping Response Control				
Intrusion Detection & Prevention (IPS)	•	•	•	٠	
WAN Modes	NAT, Classical Routing				
ISP Address Assignment	DHCP, Static IP Assignment, PPPoE, PPTP				
NAT Modes	1-1 NAT, PAT				
Routing	Static, Dynamic, RIPv1, RIPv2				
VoIP	SIP ALG				

MODEL	UTM5	UTM10	UTM25	UTM50
DDNS		DynDNS.org, TZ	O.com. Orav.net	
Firewall Functions	Port Range Forwarding, Port Triggering, DNS proxy, MAC Address Cloning/spoofing, Network Time Protocol NTP Support, Diagnostic Tools (ping, DNS lookup, trace route, other), Auto-Uplink on Switch Ports, L3 Quality of Service (QoS) ,LAN-to-WAN and WAN-to-LAN (ToS)			
DHCP	DHCP Server, DHCP Relay			
User Authentication for VPN		Active Directory, LDAP, Rad	dius, Local User Database	
Security Policies Based on Active Directory with Single Sign-On (SSO)				•
PCI Compliance Two Factor Authentication Support	٠	•	•	•
VPN				
Site to Site VPN Tunnels	5	10	25	50
Simultaneous SSL VPN Tunnels	2	5	13	25
IPsec Encrypton/Authentication		DES, 3DES, AES(128,19	2,256 bit)/SHA-1, MD5	
Key Exchange		IKE, Manual Key, Pre-S	Shared Key, PKI, X.500	
IPsec NAT Traversal (VPN Passthrough)	•	•	•	•
iPhone Native VPN Client Support	•	•	•	•
Included ProSafe VPN Client Lite Licenses	0	1	1	3
SSL Version Support	SSLv3, TLS1.0			
SSL Encryption Support	DES, 3DES, ARC4, AES(128,256 bit)			
SSL Message Integrity	MD5, SHA-1, MAC-MD5/SHA-1, HMAC-MD5/SHA-1			
SSL Certificate Support			tellman, Self	
SSL VPN Platforms Supported	Windows 2000 / 2	(P / Vista <sup>®</sup> (32bit), Window	· ·	S® X 10.4.x/10.6.x
DEPLOYMENT				•
VLAN Support	•	•	•	•
Dual-WAN Fail-over	•	•		
Intelligent Traffic Load Balancing				
Configuration Wizards		Setup, IPsec \	/PNI SSI VPNI	•
Management			SNIMP v2c	
Reporting	HTTP/HTTPS, SNMP v2c Summary Statistics, Graphical Reporting, Automatic Outbreak Alerts, Automatic Malware Notifications, System Notifications			
Logging	Traffic, Malware, Spam, Content Filter, Email Filter, System, Service, IPS, Port Scan, IM, P2P, Firewall, IPsec VPN, SSL VPN			
Log Delivery	Management GUI Query, Email Delivery, Syslog			
HARDWARE				
Gigabit RJ45 Ports WAN/LAN	1/4	1/4	2/4	2/6
DMZ Interfaces (Configurable)	1	1	1	1
Flash Memory/RAM	2 GB/512 MB	2 GB/512 MB	2 GB/1 GB	2 GB/1 GB
USB Ports	1	1	1	1
Certifications	ICSA: Anti-virus VPNC: AES Interop, Basic Interop Checkmark: Anti-Malware, Anti-Spam, Enterprise Firewall, VPN, IPS, URL Filtering			
Major Regulatory Compliance	FCC Class A, CE, WEEE, RoHS			
Storage and Operating Temperatures	Operating Temperature 0°-45° C (32°-113° F), Storage Temperature -20°-70° C (-4°-158° F)			
Humidity	Operation 90% Maximum Relative, Storage 95% Maximum Relative			
Electrical Specifications	100-240V, AC/50-60Hz, Universal Input, 1.2 Amp Max Universal Input, 1.2 Amp Max 1.0 Amp Max			
Dimensions (W x H x D) cm	33 x 4.3 x 20.9	33 x 4.3 x 20.9	33 x 4.3 x 20.9	44 x 4.3 x 26.1
Dimensions (W x H x D) in	13 x 1.7 x 8.2	13 x 1.7 x 8.2	13 x 1.7 x 8.2	17.3 x 1.7 x 10.3

ProSecure<sup>®</sup> Unified Threat Management Appliance

MODEL	UTM5	UTM10	UTM25	UTM50
Weight kg/lb	2.1/ 4.6	2.1/ 4.6	2.1/ 4.6	2.9/6.4
Package Contents	ProSecure UTM Appliance , Power Cable, Rubber Feet, Resource CD, Rackmount Kit, Warranty Card, Quick Installation Guide, Subscription Card (Bundles Only)			
Hardware Warranty	2 Years			

ORDERING INFORMATION						
Hardware (Firewall and VPN Fu	nctionality Only)					
North America		Europe		Asia		
UTM5-100NAS		UTM5-100EUS			UTM5-100AJS	
UTM10-100NAS		UTM10-100EUS	UTM10-100EUS		UTM10-100AJS	
UTM25-100NAS		UTM25-100EUS		UTM25-100AJS		
UTM50-100NAS		UTM50-100EUS		UTM50-100AJS		
1-Year Bundle (Hardware includ	ng 1-year Web, 1-ye	ear Email, and 1-year So	ftware Maintenance and Up	grades, 24/7	Support, and Advanced Replacement	
North America Europe			Asia			
UTM5EW-100NAS		UTM5EW-100EUS		UTM5EW-100AJS		
UTM10EW-100NAS		UTM10EW-100EUS		UTM10EW-	UTM10EW-100AJS	
UTM25EW-100NAS		UTM25EW-100EUS		UTM25EW-100AJS		
UTM50EW-100NAS	DEW-100NAS UTM50		A50EW-100EUS UTM50EW		-100AJS	
3-Year Bundle (Hardware includ	ng 3-year Web, 3-ye	ear Email, and 3-year So	ftware Maintenance and Up	grades, 24/7	Support, and Advanced Replacement	
North America		Europe		Asia		
UTM5EW3-100NAS		UTM5EW3-100EUS		UTM5EW3-	-100AJS	
UTM10EW3-100NAS		UTM10EW3-100EUS		UTM10EW3-100AJS		
UTM25EW3-100NAS		UTM25EW3-100EUS	SEW3-100EUS		UTM25EW3-100AJS	
UTM50EW3-100NAS		UTM50EW3-100EUS		UTM50EW3-100AJS		
1-Year Subscriptions						
Web Threat Management	Email Threat	Management	Software Maintenance and Upgrad 24/7 Support, Advanced Replacem		Subscription Bundle (Web + Email + Support & Maintenance)	
UTM5W-10000S	UTM5E-100	00S	UTM5M-10000S		UTM5B-10000S	
UTM10W-10000S	UTM10E-10	000S UTM10M-10000S			UTM10B-10000S	
UTM25W-10000S	UTM25E-10	000S	UTM25M-10000S		UTM25B-10000S	
UTM50W-10000S	UTM50E-10	000S	UTM50M-10000S		UTM50B-10000S	
3-Year Subscriptions						
Web Threat Management	Email Threat	Management	Software Maintenance and Upgrades, 24/7 Support, Advanced Replacement		Subscription Bundle (Web + Email + Support & Maintenance)	
UTM5W3-10000S	UTM5E3-10	000S	UTM5M3-10000S		UTM5B3-10000S	
UTM10W3-10000S	UTM10E3-1	0000S	UTM10M3-10000S		UTM10B3-10000S	
UTM25W3-10000S	UTM25E3-1	0000S	UTM25M3-10000S		UTM25B3-10000S	
UTM50W3-10000S	UTM50E3-1	00S UTM50M3-10000S			UTM50B3-10000S	

\*Available on the UTM25 and UTM50.

<sup>1</sup>Throughput measured in a lab environment. Actual performance may vary.

### **NETGEA**R<sup>°</sup>

350 E. Plumeria Drive San Jose, CA 95134-1911 1-888-NETGEAR (638-4327) E-mail: info@NETGEAR.com www.NETGEAR.com © 2010 NETGEAR, Inc. NETGEAR, the NETGEAR Logo, NETGEAR Digital Entertainer Logo, Connect with Innovation, FrontView, IntelliFi, PowerShift, ProSafe, ProSecure, RAIDar, RAIDiator, RangeMax, ReadyNAS, Smart Wizard, X-RAID, and X-RAID2, are trademarks and/or registered trademarks of NETGEAR, Inc. and/or subsidiaries in the United States and/or other countries. Mac and the Mac logo are trademarks of Apple Inc., registered in the U.S. and other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice. All rights reserved.

This product comes with a limited warranty, the acceptance of which is a condition of sale.